

AQUENCE XP

High-performance casein-free adhesive range for glass labeling.



Cold and humid or dry labeling
The label sticks.



Ice and cold
The label sticks.



The end of a cycle
The label comes off easily.

Benefits

- » Casein-free adhesive formulation
- » Increased efficiency through excellent machinability
- » Efficient consumption
- » Fast and easy wash-off
- » Top quality, reliability and product stability
- » Wide range of applications



AQUENCE XP

High-performance adhesive range for glass labeling.

	AQUENCE XP 150	AQUENCE XP 170	AQUENCE XP 180-22	AQUENCE XP 190	AQUENCE XP 200 Plus	AQUENCE XP 500 Plus
Application:	Based on new polymer generation, fast setting, high wet tack; suitable for aluminum foil and reusable containers	First recommendation for glass labeling on lower speed machines	Allrounder with some IWR and CWR	Based on new polymer generation, fast setting, high wet tack and IWR; suitable for aluminum foil	Very high IWR, fast setting time; one-way bottles	High coated bottles and difficult label materials
Viscosity min.:	65 000	40 000	40 000	45 000	60 000	60 000
Viscosity max.:	95 000	60 000	70 000	75 000	85 000	80 000
pH value:	7.5 - 9.0	7.5 - 8.5	7.0 - 9.0	7.0 - 9.0	7.0 - 9.0	7.3 - 8.5
Returnable bottles:	✓	✓	✓	✓	-	✓
Ice water resistance: after 7 days drying time	< 1	< 1	3 - 4	> 7	> 14	1
Wet tack:	high	low	medium	high	high	medium
Setting time:	medium	medium	medium	fast	slow	medium
CWR (fiber tear):	medium	low	medium	high	high	medium
Wet bottles:	✓	(✓)	✓	✓	✓	✓
Cleaning Properties:	++++	++++	+++	+++	++	++
Aluminum foil:	+++	+++	+++	+++	+++	+++
Adhesion:	+++	+++	+++	+++	+++	+++++
Shelf life:	12 months	6 months	12 months	12 months	12 months	12 months

» Try AQUENCE XP now! To experience how our AQUENCE XP range can improve your bottle labeling operation, please contact your local sales representative for more information and assistance with product trials.

GET IN CONTACT WITH US

www.henkel.com/consumerpackaging

Henkel AG & Co. KGaA
Henkelstraße 67
40589 Düsseldorf | Germany

Telefon: +49 211 797-0
E-Mail: labeling@henkel.com



The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention. The information is protected by copyright. In particular, any reproductions, adaptations, translations, storage and processing in other media, including storage or processing by electronic means, enjoy copyright protection. Any exploitation in whole or in part thereof shall require the prior written consent of Henkel AG & Co. KGaA. Except as otherwise noted, all marks used in this document are trademarks and/or registered trademarks of Henkel and/or its affiliates in the US, Germany, and elsewhere. © Henkel AG & Co. KGaA, 11/2021