TECHNOMELT® Supra 350 HT

High Adhesion Hot melt Packaging Adhesive
For bonding difficult materials at high speed
Runs at 160°C to 180°C

Look after your hot melt:

- Run at the right temperature
  160°C to 180°C
- Keep lids closed (tank and storage bin)

- Use set back or reduce temperature during long line stoppages

- Deal with issues early

For more assistance call or text
+44 7917 675206

www.directadhesives.co.uk www.gluegunsdirect.com
Telephone: 01525 381111 / 0161 6271001

Direct Adhesives TECHNOMELT® Tecbond Adhesives kenyon GROUP LTD

The Best Adhesive Support Team, for your packaging operation…

Technomelt Easy Flow Cleaner is an exceptional cleaner for all hot melt adhesive types, including PUR. Technomelt Easy Flow Cleaner doesn't just purge your system; it really softens and clears deposits within your complete hot melt system.

Technomelt Q1924 is a resin cleaner for all thermoplastic hot melts and allows you to safely purge your system.

Technomelt Melt-O-Clean is a citrus based cleaner for removing hot melt deposits from surfaces. It can also be used as a soak for parts such as nozzles.

Our cleaners have been thoroughly tested and approved by equipment manufacturers.

At Direct Adhesives we have the expertise to help you with your cleaning and maintenance regime, so get in touch with us, we are ready to help.

www.directadhesives.co.uk www.gluegunsdirect.com
Telephone: 01525 381111 / 0161 6271001